

SODA ASH

Calcium Contamination Remover

Product Description

SODA ASH is used in water-base mud as a source of carbonate ions to precipitate calcium, increase pH or flocculate spud mud.

SODA ASH is the common name for sodium carbonate (Na_2CO_3). It is a weak base that is soluble in water and dissociates into sodium (Na) and carbonate (CO_3) ions in solution.

Typical Physical Properties

Physical appearance	White powder
Specific gravity	2.51
pH	11.4
Solubility	572° F (300°C), 51 g/100 ml at 86°F [30°C]

Application

SODA ASH is used primarily to reduce soluble calcium in water-base drilling muds and makeup waters. Other uses include increasing pH and flocculating spud muds.

Calcium is present in many makeup waters and formations. It can cause flocculation of the mud resulting in increased rheology, gel strengths and fluid loss. In pure water, SODA ASH forms highly buffered solutions that have a pH range of 10.9-11.6 at concentrations of 0.21 to 30 lb/bbl (0.6 to 86 kg/m^3).

Carbonate ions begin being converted into bicarbonate (HCO_3) ions when the pH decreases below 11.3.

Advantages

- Widely available and economical source of carbonate ions to precipitate calcium while increase pH
- Concentrate chemical; effectively removes calcium in most drilling fluids at small treatment levels
- Effective flocculant for spud muds

Limitations

- Increases pH and should not be used to treat cement contamination or higher pH fluids; less soluble at high pH
- Over-treatment results in carbonate contamination; even minor amounts of excess carbonate ions can cause large increases in yield point, gel strengths and fluid loss

Recommended Treatment

Typical treatments of SODA ASH range from 0.25 to 2 lb/bbl (0.7 to 5.7 kg/m^3), depending on the calcium level and water chemistry of the drilling fluid. One pound (0.45 kg) of SODA ASH removes the calcium from 1.283 lb (0.58 kg) calcium sulfate (anhydrite). Treatments should be made on an incremental basis to prevent over-treatment which results in carbonate contamination.

Toxicity and Handling

Handle as an industrial chemical, wearing protective equipment and observing the precautions described in the Material Safety Data Sheet (MSDS).

SODA ASH is an alkaline material that can cause irritation to eyes, skin or respiratory tract.

SODA ASH

Calcium Contamination Remover

SODA ASH should be added slowly to the mud system either by mixing through the hopper or chemical barrel. Do not mix SODA ASH with other chemicals, especially caustic soda or lime. When using a chemical barrel, mix SODA ASH into a full barrel of freshwater and provide adequate agitation.

Packaging and Storage

SODA ASH is a globally available commercial chemical and is packaged in 100-lb (45.4-kg) and 50-lb (22.7-kg), multi-wall, paper sacks.

Store in a dry area away from water or acids.