

340K Hydraulic Snubbing Unit - Used



The 340K is a stand-alone snubbing unit designed and custom built to perform live or dead well interventions. It has the capabilities to run tubing from 2 3/8" to 9 5/8" and has 22,000 ft/lbs. rotary that allows it to take on tasks unheard of in the snubbing industry such as drilling, milling out windows for side tracks and side tracking.

Lift Capacity

- 340,000 lbs.

Slip Bowls

- Capacity - 340,000 lbs.

Workover and Snubbing Capability

- Yes

Fuel Tank

- 990 gal.

Surface Pressure Capacity

- 20,000 psi

Tongs

- Clincher 5 1/2 UHT
- Clincher 8 5/8 XHT

Jack

- 10' stroke
- Torque tubes
- Pipe guides

Pumps

- Powered with CAT 3412
- OPI 600
- GD HD 22-50
- GD PZ-7

Work Window

- 6' with 14' bore or 10' with work basket

Mud System

- 100-200 bbl. tank with mixing capabilities

HD Tong Pole

- Included

Blowout Preventers

- 7 1/16", 11", and 13 5/8" 5M-15M
- Blind shear capability

Hydraulic Gin Pole

- Capacity - 10,000 lbs.
- 55' with extension

Rotary Table

- Maximum capacity - 460,000 lbs.
- Maximum RPM - 90
- Maximum torque - 22,000 ft./lbs.

Power Units

- Quiet Pak with enclosed 85 DBA @ 1 Meter
- Power - CAT 3406 DITA
- 525 HP Funk quad drive gear box
- Dennison hyd. pumps
- Weight - 21,000 lbs. each

Auxiliary Equipment

- Substructure with skidding package

BOP Closing Unit

- Seven station, 160 gal.
- Weight - 17,000 lbs.

Choke/Squeeze Manifold

- Dual choke/Circulating

Communication/ Instrumentation

- EMS 1 PVT System
- Radio Package